

Creative Professional

from **X**XYRON

3 in 1



The Xyron Pro2500 Multi-Purpose A1/A2 Machine.

Xyron's cold lamination, encapsulation and adhesive application system

Whether applying adhesive in the studio for client presentation, mock ups, story-boards, point of purchase material or large format posters, the Xyron Pro2500 instantly applies adhesives without heat or electricity. What's more, this machine also allows double sided edge-to-edge encapsulation – meaning that artwork can be cropped to size without curling or peeling. Simply feed an item in, turn the handle and trim. No smell, no mess and no waiting. The patented roll-set system allows users to switch between applications, making the Xyron Pro2500 the most versatile machine available. Its improved adhesive formula, coupled with higher-pressure rollers, improves both transfer and bonding quality.

XXYRON
www.xyron.com

Esselte
www.esselte.co.uk

Innovate. Inspire. Create.



Advance technology rollers fitted to the Xyron Pro2500 ensure that pressure is evenly applied to every piece of artwork, guaranteeing a top quality finish every time. The machine comfortably accepts an A1 (594mm) width original.

Creative Professional from **X**XYRON

- Clean, simple, easy to use.
- For client presentation, mock ups, POP material and posters.
- Choose from permanent or re-positional adhesives.
- Single or double sided lamination.

There are six types of adhesive and lamination cartridges for you to choose from and the patented drop-in cartridge system allows you to effortlessly switch cartridges between applications.

Xyron Pro2500 Specifications

Product Code: 23652
 Footprint: 63 cm L x 86.8 cm W x 57.5 cm H x
 Document Width (Max): 63.5 cm
 Weight: 40.8 kg
 Document Length (Max): 30.5 m
 Packaged Weight: 47.6 kg
 Power Source: None
 Document Thickness (Max): 4.36 mm
 Cutter: Built in removable, replaceable cutter

AT400-300 Permanent Adhesive Transfer: A strong adhesive that creates a permanent bond on most surfaces.

AT406-170 Re-positional (Acid Free) Transfer: Allows you to re-position your item and allows for easy removal from mount boards, paper, walls and most other surfaces.

DL403-300 Double Sided Laminate: A high quality film suitable for use on a variety of substrates. The film has superior adhesion, excellent clarity and is compatible with most media.

SL403-300 Single Sided Lamination: Xyron's general use laminate with superior adhesion for a perfect finish whatever the substrate.

LAT405-300 Combination One Side Lamination/One Side Permanent Adhesive: Incorporating Xyron's general use laminate on the front with a permanent adhesive on the reverse.

LAT406-170 Combination One Side Lamination/One Side Re-positional Adhesive: Incorporates Xyron's general use laminate on the front and a re-positional adhesive on the reverse.*

2500 Cartridges.

| Esselte (Part Number) | Alpha (Part Number) | Product Description | Material Length | Material Width | Laminate & Adhesive Combination thickness (Per Side) | Mounting Adhesive Thickness | Adhesive pH | Mounting Adhesive Strength (1:10; 10 High) | PAT Approved |
|--|---------------------|--|-----------------|----------------|--|-----------------------------|----------------------------------|--|--------------|
| Adhesive Application Cartridges (AT Series): | | | | | | | | | |
| 23627 | AT400-300 | Permanent Adhesive Transfer | 90 m | 63.5 cm | N/A | 15.2 mic | 5.0 - 7.0 | 8 | Yes |
| 23628 | AT406-170 | Re-positional (Acid Free) Adhesive Transfer | 51 m | 63.5 cm | N/A | 15.2 mic | Acid Free | - | Yes |
| Double or Single Sided Lamination Cartridges (DL & SL Series): | | | | | | | | | |
| 23629 | DL403-300 | Double Sided Laminate | 90 m | 63.5 cm | 62.5 mic | N/A | 6.0 - 6.4 | N/A | Yes |
| 23630 | SL403-300 | Single Sided Laminate | 90 m | 63.5 cm | 62.5 mic | N/A | 6.0 - 6.4 | N/A | Yes |
| Combination One Side Lamination/One Side Adhesive Application (LAT Series): | | | | | | | | | |
| 23631 | LAT405-300 | 1 Side Laminate/1 Side Adhesive Application General Use Laminate/High Tack Adhesive | 90 m | 63.5 cm | 62.5 mic | 15.2 mic | Lam: 6.0 - 6.4 Adh: 5.0 - 7.0 | 8 | Yes |
| 23632 | LAT406-300 | 1 Side Laminate/1 Side Adhesive Application General Use Laminate/Re-positional | 51 m | 63.5 cm | 62.5 mic | 27.9 mic | Lam: 6.0 - 6.4 Adh: Acid Free | - | Yes |

* Please test before each application.

XXYRON
www.xyron.com

Esselte[®]
www.esselte.co.uk

Innovate. Inspire. Create.